


2-Way Compact PA Wall Speakers



PS-500T

32 WATTS


- High fidelity 2-Way, 100V multi purpose PA speaker system.
- 100V, Power taps of 32W, 16W, 8W.
- Facility to use as 8 ohms Low Impedance Speaker available.
- Power Taps can be selected through an easily accessible rotary switch.
- Weather Resistant Speaker.
- Movable mounting bracket supplied, can be mounted in vertical or horizontal positions.



PS-400T

16 WATTS


- High fidelity 2-Way, 100V multi purpose PA speaker system.
- 100V Power taps of 16W, 8W & 4W.
- Power taps can be selected through rotary switch.
- Facility to use as 8 ohms Low Impedance Speaker available.
- Weather Resistant Speaker.
- Movable mounting bracket supplied, can be mounted in vertical or horizontal positions.



PS-300T

10 WATTS

- High fidelity 2-Way, 100V multi purpose PA speaker system.
- 100V, Power taps of 6W, 3W & 1.5W
- Power taps can be selected through rotary switch.
- Facility to use as 8 ohms Low Impedance Speaker available.
- Key hole for easy wall mounting.
- Threaded brass ferrule for stand mounting.



COMMON FEATURES

- High Fidelity sound for music.
- Speaker System consists of woofer & dome tweeter.
- Elegant plastic cabinet in white colour.
- Ideal for background music in offices, banks, restaurants, showrooms etc.

SPECIFICATIONS	PS-500T	PS-400T	PS-300T
INPUT POWER	32W RMS / 48W Max.	16W RMS / 24W Max.	10W RMS / 15W Max.
RATED VOLTAGE	100V	100V	100V
POWER TAPS ON 100V	32/16/8W	16/8/4W	6/3/1.5W
LOW IMPEDANCE	8 Ω	8Ω	8Ω
FREQUENCY RESPONSE	80-20,000Hz	85-20,000Hz	150-20,000Hz
SPL at 1kHz (1W/1m)	87dB	86dB	86dB
SPEAKER	Woofer 125mm (5") Tweeter 13mm dome	Woofer 95mm (3 3/4") Tweeter 13mm dome	Woofer 75mm (3") Tweeter 13mm dome
DIMENSIONS	W178 × H252 × D144 mm	W133 × H187 × D107 mm	W95 × H141 × D100 mm
WEIGHT	2.65kg	1.40kg	0.80kg